UniChock™ Vehicle Restraint



FEATURES

- Damaged traction teeth can be replaced as necessary to maintain a stronger grip
- Automatic light sequencing with interior/ exterior red/green lights always in opposition
- Exterior and interior audible alarm if the UniChock is not in a safe position during loading
- Full communication package with lights, signs and control panel with universal signage pictures for additional communication safety
- Optional integrated iDock Controls for safe leveler interlock
- Design and manufactured in the USA

Connect online with



* UniChock[™] sample installation. Product subject to change.

Value Engineered Dock Levelers



VEHICLE RESTRAINT SYSTEM

The UniChock^M is a wheel-based trailer restraint with advanced light communication and available as a standalone unit or integrated with other dock equipment. Universally effective in most conditions, the unit helps prevent unexpected trailer departure or movement from the loading dock during the loading process.

OPERATION

Once a trailer is fully backed and parked in position against the dock bumpers, the yellow UniChock is removed from the storage bracket and placed under the front of one of the trailer's back tires. This will sound an audible indicator and display a message on the iDock[®] Controller that the unit is in a safe position. The dock attendant can then proceed to open the door and deploy the leveler.

After loading is complete, the dock attendant stores the leveler and closes the overhead door, either of which must have an installed switch interlocked with the restraint. This will then sound and display indications to return the UniChock to the storage bracket.

SAFETY FEATURES

- Damaged traction teeth can be replaced as necessary to maintain a stronger grip
- Automatic light sequencing with interior/exterior red/green lights always in opposition
- Exterior and interior audible alarms if the UniChock is not in a safe position during loading
- Full communication package with lights, signs and control panel with universal signage pictures for additional communication safety
- Optional integrated iDock Controls for safe leveler interlock



Secure grip to the ground with audible indicators if in unsafe position during loading.

LIGHT COMMUNICATION

The UniChock uses advanced iDock[®] Controls with an LED 3-color light communication system. As a truck approaches, the exterior light is green and the interior light is red. Once the trailer is restrained, the interior light changes to green and exterior light to red, warning the driver not to pull away from the dock. When the trailer is released and the restraint hook is safely stored, the lights revert back to a green exterior and red interior. An interior amber "caution" light is used if needed for bypass mode or faults.

CONSTRUCTION & ELECTRICAL

The restraint unit is durable and light weight aluminum with a powder coat finish. The traction teeth and storage bracket are zinc-plated steel. Wired sensors are installed in the restraint unit and the storage bracket. The control panel is NEMA 4X with all components, connections and wiring UL-listed and/or recognized. Panels are built in-house in a UL-approved control panel shop.



UNICHOCK[™] COMMON OPTIONS

Bracket extension for alternative storage positions Connect online with myQ Enterprise Custom interlock sequence with leveler and/or door Integrated control panel

W194N11481 McCormick Dr. | Germantown, WI 53022 dlmdocks.com | sales@dlmdocks.com 800-643-5424



Designed, Engineered, and Manufactured in the U.S.A. © 2024 Systems, LLC/DLM Consistent with our policy of continuing product improvement, we reserve the right to change product specifications without notice or obligation.



Value Engineered Dock Levelers