


Wheel Chock Wheel Restraint Unit



FEATURES

- Help prevent a truck trailer from rolling
- Available in laminated rubber, molded rubber or molded urethane
- Lightweight and durable
- Available with a chain and optional cradle
- Resistant to extreme weather conditions
- Easy to use
- Meets OSHA standards
- Use in conjunction with RIG-based vehicle restraints

Value Engineered Dock Levelers



Wheel Chock Wheel Restraint Unit



MODEL 88-8

- Extra heavy-duty
- Laminated rubber pads assembled on 3/4" (19.1mm) bolts and compressed between 1/4" (6.35mm) steel plates
- · Contoured to fit tire
- Fully meets OSHA requirements
- Completely reversible
- Constructed of fabric reinforced rubber pads cut from recycled truck tires
- Available with chain
- Weight: 15lbs (6.80kg) each
- * NOTE: also available with gripper cleats for better traction in snow, ice, dirt and mud



MODEL 68-9

- Molded from a tough fabric reinforced rubber compound
- Well suited for trailer truck and other heavy equipment
- Economical and long lasting
- Easy on macadam surfaces
- Available with chain
- Weight: 10lbs (4.54kg) each



MODEL 811-7

- Light weight yet heavy-duty
- Molded urethane chock contoured to fit truck tires
- Designed to grip both the tire and the pavement
- Will not harm macadam
- Weight: 6.5lbs (2.95kg) each

Model	A Width	B Height	C Length	Weight	Color
88-8	8" (203.2mm)	8" (203.2mm)	8" (203.2mm)	15lbs (6.80kg)	black
68-9	8" (203.2mm)	5 ^{3/4} " (146mm)	9" (228.6mm)	9lbs (4.8kg)	black
811-7	11 ^{3/8} " (295.3mm)	8 ^{1/4} " (209.6mm)	7 ^{5/8} " (193.7mm)	6.5lbs (2.95kg)	orange

W194N11481 McCormick Dr. | Germantown, WI 53022 dlmdocks.com | sales@dlmdocks.com 800-643-5424



dlmdocks.com

Designed, Engineered, and Manufactured in the U.S.A.
© 2024 Systems, LLC/DLM
Consistent with our policy of continuing product improvement, we reserve the right to change product specifications without notice or obligation.



Value Engineered

Dock Levelers